

### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property **Organization**

International Bureau



# 1 (1888 11) (1881 1 (1881 1 1891 1 1891 1 1891 1 1991 1 1991 1 1991 1 1991 1 1991 1 1991 1 1991 1 1991 1 1991 1

#### (43) International Publication Date 25 March 2004 (25.03.2004)

**PCT** 

### (10) International Publication Number WO 2004/025691 A1

(51) International Patent Classification7: 61/12

H01J 61/82,

(21) International Application Number:

PCT/IB2003/003851

- (22) International Filing Date: 29 August 2003 (29.08.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

- (30) Priority Data:
  - 102 42 203.6


10 September 2002 (10.09.2002)

- (71) Applicant (for DE only): PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH [DE/DE]; Steindamm 94, 20099 Hamburg (DE).
- (71) Applicant (for all designated States except DE, US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): SCHÖLLER, Klaus [DE/DE]; c/o Philips Intellectual Property &

Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE). GERVELMEYER, Rolf [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).

- (74) Agent: MEYER, Michael; Philips Intellectual Property & Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]



least two electrodes extending into the discharge chamber, and possibly an outer bulb surrounding the inner vessel, wherein the discharge chamber contains an ionizable filling comprising: - at least one rare gas, - 0 mg to 10 mg of mercury, and - a metal halide mixture comprising: \* 40 to 80% by weight of sodium halide, \* 25 to 55% by weight of scandium halide, \* 1 to 15% by weight of indium halide, and \* 0 to 34% by weight of thallium halide.

